



Flexible Filler 300G

Technical Data Sheet

Description

Bartoline Flexible Filler is a quick drying interior decorators filler that can be overpainted with emulsion paint within 1-2 hours of application. Adheres to most surfaces and remains permanently flexible to prevent unsightly cracks developing after decorating. Bartoline Flexible Filler conforms to the harmonised European standard EN 15651-1 for façade interior applications.

Applications

Bartoline Flexible Filler has been specially developed for sealing interior gaps or cracks where movement can occur such as between plaster work, window frames, doorframes, skirting boards, architraves, fitted furniture etc. Use prior to painting or papering to prevent unsightly cracks developing at a later stage.

Directions

Work tube between fingers before opening. Remove cap and carefully cut nozzle to the required angle. Squeeze the tube directly into the gap to give a good solid fill and level with a filling knife. Smooth down within 10 minutes using a lightly wetted spatula before a skin has started to form. Do not saturate the surface with water, as this will delay the curing process. Can be overpainted with emulsion paint as soon as a skin forms (approximately 1 hour), allow 24 – 48 hours for oil/solvent-based paints. Replace cap after use. Clean tools with water. Store any unused filler in a cool, frost free place.

Health and Safety

See MSDS for full information.

Technical Data

Form	Ready to use paste
Viscosity	4500 - 5000 Poise Lamy - MSR4
Elongation at Break (%)	>100% to ISO8339
Tack Free Time	15 to 60 mins, dependent on thickness, ambient temperature and humidity
Full Cure	1 to 2 days, dependent on thickness, ambient temperature and humidity
Application Temp. Range	+5°C to +35°C
Service Temp. Range	-15°C to +75°C
pH	7.5-8.5
Resistance to Flow	≤ 5 mm

Packing Specification

<u>Colour</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
White	52720505	5010789720506	05010789558550	16	236	1416	59	4

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes