

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : BARTOLINE METHYLATED SPIRITS
REACH registration No : 01-2119457610-43
Product code : 4562

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Fuel for camping stoves and fondues. Glass cleaner.

1.2.2. Uses advised against

Restrictions on use : Cosmetics, personal care products

1.3. Details of the supplier of the safety data sheet

Manufacturer

Bartoline Limited Ltd
Barmston Close
HU17 0LW Beverley
United Kingdom
T 01482 678710 - F 01482 872606
infor@bartoline.co.uk - www.bartoline.co.uk

EU Address

Bartoline Ireland Limited
Unit 3D North Point House
North Point Business Park
New Mallow Road
Cork T23 AT2P
Ireland
+353212066441
info@bartoline.eu

1.4. Emergency telephone number

Emergency number : 01482 678710
8.30am - 4.45pm Monday to Friday
NHS 111 - General Public (24 Hour service)

| Country | Organisation/Company | Address | Emergency number | Comment |
|---------|--|--|--|---------|
| Ireland | National Poisons Information Centre Beaumont Hospital | PO Box 1297 Beaumont Road 9 Dublin | +353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7) | |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Full text of H- and EUH-statements: see section 16

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0


Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P264 - Wash hands, forearms and face thoroughly after handling.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.
P103 - Read carefully and follow all instructions.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|----------------|---|
| ethanol substance with a Community workplace exposure limit | CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 | ≥ 80 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 |
| propan-2-ol substance with a Community workplace exposure limit | CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 | $\geq 1 - < 5$ | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|-----------|---|
| butanone substance with a Community workplace exposure limit | CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 | ≥ 1 – < 5 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 |

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures general | : Remove victim to uncontaminated area. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Move the affected person away from the contaminated area and into the fresh air. Get medical advice/attention. Give oxygen or artificial respiration if necessary. |
| First-aid measures after skin contact | : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Wash with plenty of water/.... |
| First-aid measures after eye contact | : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing. |
| First-aid measures after ingestion | : Get immediate medical advice/attention. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Keep at rest. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Symptoms/effects after inhalation | : At high concentrations, the vapours can be irritating to the respiratory system. May have a narcotic effect at high concentrations. Other symptoms: Headache, dizziness, nausea, unconsciousness. |
| Symptoms/effects after skin contact | : Repeated exposure may cause skin dryness or cracking. Irritation. |
| Symptoms/effects after eye contact | : Eye irritation. Redness. |
| Symptoms/effects after ingestion | : Ingestion may cause nausea and vomiting. Abdominal pain, nausea. Swallowing a small quantity of this material will result in serious health hazard. Liquid with low viscosity. May result in aspiration into the lungs. Product entering lungs lead to the rapid development of very serious inhalation pulmonary lesions (medical survey during 48 hours). |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| Fire hazard | : Heavier than air, vapours may travel long distances along ground, ignite and flash back to source. Highly flammable liquid and vapour. |
| Explosion hazard | : Solvent vapours may form explosive mixture with air. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Hydrocarbons. Aldehydes. Soot. Gas may accumulate in confined areas. Harmful if inhaled. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

5.3. Advice for firefighters

| | |
|--------------------------------|---|
| Precautionary measures fire | : Avoid breathing (dust, vapor, mist, gas). |
| Firefighting instructions | : Cool laterally with water containers exposed to flames, even after the fire is extinguished. |
| Protection during firefighting | : Wear fire/flame resistant/retardant clothing. In confined space use self-contained breathing apparatus. Full face piece respirator. |
| Other information | : Keep run-off water out of sewers and water sources. Containers close to fire should be removed or cooled with water. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area.

6.1.1. For non-emergency personnel

| | |
|----------------------------------|--|
| Protective equipment | : Keep unnecessary and unprotected personnel away from the spillage. |
| Emergency procedures | : Land spill. Eliminate all ignition sources. Stop leak if safe to do so. Do not touch or walk on the spilled product. |
| Measures in case of dust release | : Not applicable. |

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. Wear recommended personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : For further information refer to section 8: "Exposure controls/personal protection". More detailed information: See section 11. For disposal of residues refer to section 13 : Disposal considerations " ". |

6.2. Environmental precautions

Avoid release to the environment. Very toxic to aquatic life with long lasting effects. Material insoluble in water. may spread in water systems. Do not discharge into drains or the environment. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|--|
| For containment | : Eliminate sources of ignition. No open flames. No smoking. |
| Methods for cleaning up | : Stop leak if safe to do so. Absorb excess liquid spillage on inorganic adsorbent material such as fine sand, brick dust etc. Place spent adsorbent in sealed packages and contact specialist waste disposal contractor. Cover the spilled liquid product with foam to slow down evaporation. Use type. Alcohol resistant foam. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-------------------------------|---|
| Precautions for safe handling | : Avoid contact with skin and eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Eliminate all ignition sources if safe to do so. Use explosion-proof equipment. Containers must be properly grounded before beginning transfer. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

7.2. Conditions for safe storage, including any incompatibilities

| | |
|---------------------------|---|
| Technical measures | : Ground/bond container and receiving equipment. |
| Storage conditions | : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Keep locked up and out of reach of children. |
| Incompatible products | : Oxidizing agent. |
| Heat and ignition sources | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| Storage area | : Keep away from food, drink and animal feedingstuffs. |
| Packaging materials | : Carbon steel. Glass. Mild steel. Stainless steel. high density polyethylene (HDPE). Polyethylene terephthalate (PET). |

7.3. Specific end use(s)

Section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| ethanol (64-17-5) | |
|--|------------------------|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| IOEL TWA | 1920 mg/m ³ |
| IOEL TWA [ppm] | 1000 ppm |
| propan-2-ol (67-63-0) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| IOEL TWA | 999 mg/m ³ |
| IOEL TWA [ppm] | 400 ppm |
| IOEL STEL | 1250 mg/m ³ |
| IOEL STEL [ppm] | 500 ppm |
| butanone (78-93-3) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| IOEL TWA | 600 mg/m ³ |
| IOEL TWA [ppm] | 200 ppm |
| IOEL STEL | 899 mg/m ³ |
| IOEL STEL [ppm] | 300 ppm |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

| ethanol (64-17-5) | |
|--|--------------------------|
| DNEL/DMEL (Workers) | |
| Long-term - systemic effects, dermal | 343 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 950 mg/m ³ |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

| ethanol (64-17-5) | |
|--|---------------------------|
| DNEL/DMEL (General population) | |
| Long-term - systemic effects, oral | 87 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 114 mg/m ³ |
| Long-term - systemic effects, dermal | 206 mg/kg bodyweight/day |
| butanone (78-93-3) | |
| DNEL/DMEL (Workers) | |
| Long-term - systemic effects, dermal | 1161 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 600 mg/m ³ |
| DNEL/DMEL (General population) | |
| Long-term - systemic effects, oral | 31 mg/kg bodyweight/day |
| Long-term - systemic effects, inhalation | 106 mg/m ³ |
| Long-term - systemic effects, dermal | 412 mg/kg bodyweight/day |
| PNEC (Water) | |
| PNEC aqua (freshwater) | 55.8 mg/l |
| PNEC aqua (marine water) | 55.8 mg/l |
| PNEC aqua (intermittent, freshwater) | 55.8 mg/l |
| PNEC (Sediment) | |
| PNEC sediment (freshwater) | 284.74 mg/kg dwt |
| PNEC sediment (marine water) | 284.7 mg/kg dwt |
| PNEC (Soil) | |
| PNEC soil | 22.5 mg/kg dwt |
| PNEC (Oral) | |
| PNEC oral (secondary poisoning) | 1000 mg/kg food |
| PNEC (STP) | |
| PNEC sewage treatment plant | 709 mg/l |

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Ensure that there is a suitable ventilation system. Mechanical ventilation is recommended. Avoid inhalation of vapours.

8.2.2. Personal protection equipment

Personal protective equipment:

Do not attempt to take action without suitable protective equipment. Appropriate engineering controls.

Personal protective equipment symbol(s):



BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

| Eye protection | | | |
|--|----------------------|-------------------|----------|
| Type | Field of application | Characteristics | Standard |
| Use splash goggles when eye contact due to splashing is possible | Droplet | With side shields | EN 166 |

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. Nitrile-rubber protective gloves. Polyvinylchloride (PVC). Viton

Other skin protection

Materials for protective clothing:

Use appropriate personal protection equipment (PPE). According to the conditions of use, protective gloves, apron, boots, head and face protection must be worn

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear respiratory protection.

| Respiratory protection | | | |
|-----------------------------|---|-------------------|----------|
| Device | Filter type | Condition | Standard |
| Wear respiratory protection | Type A - High-boiling (>65 °C) organic compounds, Type P2 | Vapour protection | EN 405 |

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Do not exceed the occupational exposure limits (OEL). Assure that emissions are compliant with all applicable air pollution control regulations. Emission reduction measures for the specific use situation has to be evaluated: Gas absorbers and scrubbers for relatively small volume structures. Minimisation of the fumigated volume by inflated balloons for large volume structure (e.g. churches, houses). (fumigation). Control measures to prevent releases. Keep container tightly closed. Dispose of this material and its container at hazardous or special waste collection point.

Other information:

Pregnant/breastfeeding women working with the product must not be in direct contact with the product. Persons suffering from asthma or eczema and persons who have chronic lung diseases, skin or respiratory allergies to isocyanates should not work with the material.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|--------------------|
| Physical state | : Liquid |
| Colour | : Violet. |
| Appearance | : Coloured liquid. |
| Odour | : Not available |
| Odour threshold | : Not available |
| Melting point | : -114 °C |
| Freezing point | : Not available |
| Boiling point | : Not available |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

| | |
|---|-----------------------|
| Flammability | : Not available |
| Explosive limits | : Not available |
| Lower explosion limit | : Not available |
| Upper explosion limit | : Not available |
| Flash point | : ≈ 12 °C Closed cup. |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| pH | : Not available. |
| Viscosity, kinematic | : Not available |
| Viscosity, dynamic | : ≈ 1.2 mPa.s |
| Solubility | : Not available |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Vapour pressure | : 5.8 kPa |
| Vapour pressure at 50 °C | : Not available |
| Density | : 0.79 – 0.82 kg/l |
| Relative density | : Not available |
| Relative vapour density at 20 °C | : 1.03 |
| Particle characteristics | : Not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

May react with: Strong Acids. Strong oxidising agents.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May react with: Strong Acids. Strong oxidising agents.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Never pressurise packagings as they will not resist.

10.5. Incompatible materials

Acids. Oxidizing agent.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

| ethanol (64-17-5) | |
|-------------------|---|
| LD50 oral rat | 10470 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 9720 - 11380 |

| propan-2-ol (67-63-0) | |
|-----------------------|--|
| LD50 oral rat | 5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity) |

| | |
|-----------------------------------|--|
| Skin corrosion/irritation | : Not classified pH: Not available. |
| Serious eye damage/irritation | : Causes serious eye irritation. pH: Not available. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |

| propan-2-ol (67-63-0) | |
|-----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

| butanone (78-93-3) | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

STOT-repeated exposure : Not classified

| ethanol (64-17-5) | |
|----------------------------|--|
| LOAEL (oral, rat, 90 days) | 3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEL (oral, rat, 90 days) | 1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other: |

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

| ethanol (64-17-5) | |
|----------------------|--|
| EC50 - Crustacea [1] | > 10000 mg/l Test organisms (species): Daphnia magna |
| EC50 96h - Algae [1] | ≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |

| butanone (78-93-3) | |
|----------------------|---|
| LC50 - Fish [1] | 2993 mg/l Test organisms (species): Pimephales promelas |
| EC50 - Crustacea [1] | 308 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | 1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

butanone (78-93-3)

EC50 96h - Algae [1]

2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

HP Code

: HP3 - "Flammable:"

- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information


In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID |
|-------------------------------------|----------------|----------------|----------------|----------------|
| 14.1. UN number or ID number | | | | |
| UN 1170 | Not applicable | Not applicable | Not applicable | Not applicable |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet


according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

| ADR | IMDG | IATA | ADN | RID |
|--|----------------|----------------|----------------|----------------|
| 14.2. UN proper shipping name | | | | |
| ETHANOL (ETHYL ALCOHOL) / ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)) | Not applicable | Not applicable | Not applicable | Not applicable |
| Transport document description | | | | |
| UN 1170 ETHANOL (ETHYL ALCOHOL) / ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) (ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)), 3, II, (D/E) | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.3. Transport hazard class(es) | | | | |
| 3 | Not applicable | Not applicable | Not applicable | Not applicable |
|  | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.4. Packing group | | | | |
| II | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: No | Not applicable | Not applicable | Not applicable | Not applicable |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 144, 601
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

Tunnel restriction code (ADR) : D/E
EAC code : •2YE

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 100 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

| Name | CN designation | CAS-No. | CN code | Category | Threshold | Annex |
|-------------------|----------------|---------|------------|------------|-----------|---------|
| Methylethylketone | Butanone | 78-93-3 | 2914 12 00 | Category 3 | | Annex I |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

15.1.2. National regulations

France

| Occupational diseases | |
|-----------------------|---|
| Code | Description |
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

Germany

Water hazard class (WGK)

: WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510)

: LGK 3 - Flammable liquids.

Joint storage table

| | | | | |
|----------|---------|----------|----------|-----------|
| LGK 1 | LGK 2A | LGK 2B | LGK 3 | LGK 4.1A |
| LGK 4.1B | LGK 4.2 | LGK 4.3 | LGK 5.1A | LGK 5.1B |
| LGK 5.1C | LGK 5.2 | LGK 6.1A | LGK 6.1B | LGK 6.1C |
| LGK 6.1D | LGK 6.2 | LGK 7 | LGK 8A | LGK 8B |
| LGK 10 | LGK 11 | LGK 12 | LGK 13 | LGK 10-13 |

Joint storage not permitted for

: LGK 1, LGK 2A, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1C, LGK 5.2, LGK 6.1B, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for

: LGK 5.1B, LGK 6.1D, LGK 11, LGK 10-13.

Joint storage permitted for

: LGK 2B, LGK 3, LGK 6.1A, LGK 6.1C, LGK 8A, LGK 8B, LGK 10, LGK 12, LGK 13.

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category

: A(4) - low hazard for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen

: ethanol is listed

SZW-lijst van mutagene stoffen

: None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: ethanol is listed

SZW-lijst van reprotoxische stoffen –

: ethanol is listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

: ethanol is listed

Denmark

Classification remarks

: Emergency management guidelines for the storage of flammable liquids must be followed

Switzerland

Storage class (LK)

: LK 3 - Flammable liquids

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

| | |
|--------------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

BARTOLINE METHYLATED SPIRITS

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/8/2022 Version: 1.0

Full text of H- and EUH-statements:

| | |
|-----------|--|
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |
|-----------|--|

Indication of changes:

Due to change of classification database the revision numbering has been reset. You should therefore look at the revision date rather than the revision number to ensure you have the most up to date version.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.