Ready to Use All Purpose Filler
Technical Data Sheet

Description

Bartoline Ready to Use All Purpose Filler is suitable for interior and exterior use. Ideal for repairs to plaster, plasterboard, brick, wood, stone, etc. Easy to use and sand down, dries white.

Directions

Application: Ensure surfaces to be filled are clean, dry and dust free. If necessary, stir filler before use. In larger areas, apply filler in layers no more than 6mm thick, allowing each layer to set before applying the next. Fill slightly proud of surrounding surface and when fully set sand down to a fine finish. When used outdoor seal the filler with an oil-based paint, protect the filled area from rain and water until sealed. Do not use on surfaces regularly under water.

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity	3500 - 4300 Poise	Lamy - MSR4

Packing Specification

Pack Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
600g tub	52720351	5010789720353	05010789629366	6	160	960	20	8
1kg tub	52720361	5010789720360	05010789822491	6	96	576	12	8
2.5kg tub	52729230	5010789729233	05010789173760	6	42	252	7	6

Bartoline Limited, Barmston Close, Beverley HU17 0LW, England. Tel: 01482 678710 | Fax: 01482 872606 | E-mail: info@bartoline.co.uk

VERSION 4 DATED 04.12.2018

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes