



Ready to Use Instant Filler

Technical Data Sheet

Description

Ready to Use Instant Filler is suitable for interior and exterior use. Ideal for repairs to plaster, plasterboard, brick, wood and stone. Easy to use and sand down. Dries white.

Directions

Preparation:

Ensure surfaces to be filled are clean, dry and dust free. Cover nails and screw heads with an oil-based primer to prevent rusting.

Application:

Work the tube well between fingers. Remove cap and cut off tip of nozzle at a 45° angle, gently squeeze product into area to be filled and level with a filling knife or scraper. Once dry, smooth with sandpaper. In larger areas, apply filler in layers of no more than 6mm thick, allowing each layer to set before applying the next. If used on exposed outside surfaces seal filler with an oil-based paint. Protect from rain and water until sealed. Do not use on surfaces regularly under water.

Cleaning & Storage

Clean tools with water before filler sets hard. After use, ensure cap is firmly replaced.

PROTECT FROM FROST

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity	2900 - 3600 Poise	Lamy - MSR4

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
330g tube	52729161	5010789729165	05010789630492	6	236	1416	59	4

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes