



Superstik Solvent-Free Grab Adhesive 300g Squeezy Tube

Technical Data Sheet

Description

Bartoline Superstik Grab Adhesive is a ready to use solvent free adhesive, based on acrylic dispersions, which adheres to most common building surfaces and replaces nails and screws in many applications. At least one surface should be porous. Not suitable for fixing mirrors.

Applications

Bartoline Superstik Grab Adhesive Ideal for fixing skirting boards, dado rails, work tops, architraves, decorative wall panels, plasterboard, carpet grippers, covings, wood and general construction work.

Directions

Surfaces should be sound, dry, clean and free from damp, dust and grease. Gloss painted surfaces should be sanded to provide a key. Work tube well between fingers before opening. Remove cap and carefully cut nozzle to the required angle. Squeeze the tube to extrude the adhesive. Apply to one side only. Bring the components together as soon as possible, pressing firmly. When fixing heavy items or to uneven surfaces, use temporary support until the adhesive dries. Excess material can be removed with water before drying is complete. Dries in approximately 24 hours. Replace cap after use. Clean tools with water. Store any unused adhesive in a cool, frost-free place.

Health & Safety

Refer to MSDS for full information.

Technical Data

Base	Acrylic dispersion
Colour	White
Viscosity	4000 - 4500 Poise Lamy - MSR4
Density	1.575 - 1.775g/l
Open time	Approx. 60 mins
Curing time	Approx. 24 hours
Application Temp. Resistance	+5°C to +40°C
pH	7.5 - 8.5

Packing Specification

<u>Colour</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
White	52800060	5010789800062	05010789333126	6	236	1416	59	4

Customs Tariff Code

3506 1000

Shipping Classification

Not classified as hazardous for transportation