



## Boiled Linseed Oil Technical Data Sheet

### Description

Bartoline Boiled Linseed Oil is especially suitable for use on soft wood garden furniture. The oil protects wood from drying out after long periods in the sun and gives it a natural sheen that lasts. Boiled Linseed Oil contains additives to speed up the drying process. Hardwoods such as Oak and Teak should be treated with Bartoline Teak Oil.

### Preparation

Ensure that the surface to be treated is clean and dry. Remove any paint or stain with sandpaper. Wipe the surface with a cloth dampened with White Spirit to remove any grease or dirt. Treat any mildew etc. with Bartoline Fungicidal Wash.

### Application

Apply Bartoline Boiled Linseed Oil liberally using a clean cloth or brush and rub in well, remove excess. For best results apply 2 or 3 coats allowing 24 hours between coats.

### After Care

Soiled application cloths should not be left where they may constitute a fire hazard as they can be liable to self-igniting without warning. Immediately after use, wash all cloths with soapy water and dispose of safely outside. Clean equipment with Bartoline White Spirit.

### Health and Safety

See MSDS for full information.

### Technical Data

Measurement	Value	Test Method
Physical State	Liquid	Visual
Colour	Brown	Visual
Odour	Distinctive oil type	
Flash point	>100°C	
VOC content	None	
Density	0.942 ± 0.01	

### Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
250ml	26464890	5010789464899	05010789419714	12	174	2088	29	6
500ml	26464940	5010789464943	05010789450588	6	144	864	36	4
2 Litre	26465360	5010789465360	05010789465377	8	44	352	11	4
5 Litre	26465170	5010789465179	05010789465186	4	40	160	10	4
20 Litre	26462070	N/A	N/A	N/A	N/A	42	14	3
205 Litre	26460500	N/A	N/A	N/A	N/A	4	4	1

### Customs Tariff Code

1515 1910

### Shipping Classification

Non-Hazardous for shipping purposes