

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR
Product code : 4602

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Filler, plaster

1.2.2. Uses advised against

Restrictions on use : Not to be used for making casts of body parts, during setting the product may heat up causing skin burns.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Bartoline Limited Ltd
Barmston Close
HU17 0LW Beverley
United Kingdom
T 01482 678710 - F 01482 872606
infor@bartoline.co.uk - www.bartoline.co.uk

EU Address

Bartoline Ireland Limited
Unit 3D North Point House
North Point Business Park
New Mallow Road
Cork T23 AT2P
Ireland
+353212066441
info@bartoline.eu

1.4. Emergency telephone number

Emergency number : 01482 678710
8.30am - 4.45pm Monday to Friday
NHS 111 - General Public (24 Hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

EUH-statements : contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
EUH208 - Contains 1,2-benzisothiazol-3(2H)-one (2634-33-5) (3209), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9) (3292), 2-methylisothiazol-3(2H)-one (2682-20-4) (4538). May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	$\geq 0.01 - < 0.1$	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9	< 0.01	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 2 (Inhalation), H330 (ATE=0.05 mg/l/4h) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 EUH071
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5	< 0.01	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 2 (Dermal), H310 (ATE=50 mg/kg bodyweight) Acute Tox. 2 (Inhalation), H330 (ATE=0.05 mg/l/4h) Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	(0.05 ≤C ≤ 100) Skin Sens. 1, H317
2-methylisothiazol-3(2H)-one	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 (0.06 ≤C < 0.6) Skin Irrit. 2, H315 (0.06 ≤C < 0.6) Eye Irrit. 2, H319 (0.6 ≤C ≤ 100) Skin Corr. 1C, H314 (0.6 ≤C ≤ 100) Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Non hazardous mixture.
First-aid measures after inhalation	: Inhalation unlikely. Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Take off contaminated clothing. Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove any contact lenses and open eyelids wide apart. Rinse opened eye for several minutes under running water. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Drink plenty of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Under normal conditions of use, no adverse effects to health have been observed.
Symptoms/effects after inhalation	: May cause respiratory irritation. Cough.
Symptoms/effects after skin contact	: Repeated or prolonged skin contact may cause irritation. Repeated or prolonged skin contact can result in sensitisation in susceptible individuals.
Symptoms/effects after eye contact	: Eye irritation. Redness, pain.
Symptoms/effects after ingestion	: Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: The product is non-combustible. Use extinguishing agent suitable for surrounding fire.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Keep run-off water out of sewers and water sources. Containers close to fire should be removed or cooled with water.
Explosion hazard	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Hydrocarbons. Aldehydes. Soot. Gas may accumulate in confined areas. Harmful if inhaled.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Avoid breathing (dust, vapor, mist, gas).
-----------------------------	---------------------------------------------

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

Firefighting instructions	: Cool laterally with water containers exposed to flames, even after the fire is extinguished.
Protection during firefighting	: Wear fire/flammable resistant/retardant clothing. In confined space use self-contained breathing apparatus. Full face piece respirator.
Other information	: Keep run-off water out of sewers and water sources. Containers close to fire should be removed or cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Keep unnecessary and unprotected personnel away from the spillage.
Emergency procedures	: Do not touch or walk on the spilled product.
Measures in case of dust release	: Not applicable.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Wear recommended personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: For further information refer to section 8: "Exposure controls/personal protection". More detailed information: See section 11. For disposal of residues refer to section 13 : Disposal considerations " "

6.2. Environmental precautions

Do not discharge into drains or the environment. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

For containment	: Contain and collect as any solid.
Methods for cleaning up	: Scrape up material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Read label before use. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. Avoid inhalation of dust and contact with skin and eyes. In order to avoid inhalation of dust, all sanding must be done wearing adequate respirator.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Hand cream.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: No special storage required. Keep only in original container.
--------------------	-----------------------------------------------------------------

7.3. Specific end use(s)

Section 1.

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.966 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6.81 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	1.2 mg/m ³
Long-term - systemic effects, dermal	0.345 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	4.03 µg/l
PNEC aqua (marine water)	0.403 µg/l
PNEC aqua (intermittent, freshwater)	1.1 µg/l
PNEC aqua (intermittent, marine water)	110 ng/l
PNEC (Sediment)	
PNEC sediment (freshwater)	49.9 µg/kg dw
PNEC sediment (marine water)	4.99 µg/kg dw
PNEC (Soil)	
PNEC soil	3 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1.03 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0.04 mg/m ³
Long-term - local effects, inhalation	0.02 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	0.11 mg/kg bodyweight/day
Acute - local effects, inhalation	0.04 mg/m ³
Long-term - systemic effects, oral	0.09 mg/kg bodyweight/day
Long-term - local effects, inhalation	0.02 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	3.39 µg/l

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
PNEC aqua (marine water)	3.39 µg/l
PNEC aqua (intermittent, freshwater)	3.39 µg/l
PNEC aqua (intermittent, marine water)	3.39 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.027 mg/kg dwt
PNEC sediment (marine water)	0.027 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.01 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0.23 mg/l
3-iodo-2-propynyl butylcarbamate (55406-53-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	0.07 mg/m ³
Acute - local effects, inhalation	1.16 mg/m ³
Long-term - systemic effects, dermal	2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.023 mg/m ³
Long-term - local effects, inhalation	1.16 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.0005 mg/l
PNEC aqua (marine water)	0.000046 mg/l
PNEC aqua (intermittent, freshwater)	0.00053 mg/l
PNEC aqua (intermittent, marine water)	0.00053 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.017 mg/kg dwt
PNEC sediment (marine water)	0.0016 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.005 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0.44 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure adequate ventilation, especially in confined areas.

8.2.2. Personal protection equipment

Personal protective equipment:

Do not attempt to take action without suitable protective equipment. Appropriate engineering controls.

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Use splash goggles when eye contact due to splashing is possible	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Not required for normal conditions of use

Hand protection:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes. Gloves

Other skin protection

Materials for protective clothing:

Not required for normal conditions of use

8.2.2.3. Respiratory protection

Respiratory protection:

Where excessive dust may result, use approved respiratory protection equipment. In order to avoid inhalation of dust, all sanding must be done wearing adequate respirator. Dust production: dust mask with filter type P1

8.2.2.4. Thermal hazards

Thermal hazard protection:

Not applicable.

8.2.3. Environmental exposure controls

Other information:

Persons susceptible to allergic reactions should not handle this product. Always wash hands after handling the product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white. off-white.
Appearance	: Paste.
Odour	: Barely perceptible.
Odour threshold	: No information available.
Melting point	: Not available.
Freezing point	: Not available
Boiling point	: 100 °C
Flammability	: Not applicable
Explosive properties	: Not explosive.
Oxidising properties	: Not oxidising.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

Flash point	: > 100 °C
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
pH	: No information available.
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 4000 – 4900 cP Lamy MS-R4
Solubility	: soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: No Information available.
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: 1.69 – 1.79
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	: 0.0408 %
Volatility	: Water based.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Protect from freezing. No dangerous reactions known under normal conditions of use.

10.5. Incompatible materials

No dangerous reactions known under normal conditions of use.

10.6. Hazardous decomposition products

In case of fire, irritating fumes come free.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Additional information	: The product has been assessed following the conventional method and is not classified for toxicological hazards accordingly. This product has low toxicity. Only large volumes may have adverse impact on human health.

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation : Not classified
pH: No information available.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
pH	3.43 Temp.: 20 °C Concentration: 10 g/L

Serious eye damage/irritation : Not classified
pH: No information available.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
pH	3.43 Temp.: 20 °C Concentration: 10 g/L

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)

STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
LOAEL (dermal, rat/rabbit, 90 days)	0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not expected to be hazardous to the environment. However, large or frequent spills may have hazardous effects on the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified
Not rapidly degradable

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	≈ 16.7 mg/l Test organisms (species): Cyprinodon variegatus

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.94 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
LC50 - Fish [1]	0.19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0.16 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'

12.2. Persistence and degradability

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Persistence and degradability	Not biodegradable.
-------------------------------	--------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

No additional information available

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

VOC Directive (2004/42)

VOC content : 0.0408 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.

Joint storage table :

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C.

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.

Hazardous Incident Ordinance (12. BImSchV) :

Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category :

A(4) - low hazard for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen :

None of the components are listed

SZW-lijst van mutagene stoffen :

None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding :

None of the components are listed

SZW-lijst van reprotoxische stoffen –

None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling :

None of the components are listed

Denmark

Danish National Regulations :

Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) :

LK 10/12 - Liquids

15.2. Chemical safety assessment

No additional information available

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

SECTION 16: Other information

Indication of changes:

Due to change of classification database the revision numbering has been reset. You should therefore look at the revision date rather than the revision number

to ensure you have the most up to date version.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one (2634-33-5) (3209), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9) (3292), 2-methylisothiazol-3(2H)-one (2682-20-4) (4538). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

Indication of changes:

Due to change of classification database the revision numbering has been reset. You should therefore look at the revision date rather than the revision number to ensure you have the most up to date version.

1876 THE PROFESSIONAL RANGE - PLASTER SKIM & REPAIR

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12/14/2022 Version: 1.0

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.