



— 1876 —
THE PROFESSIONAL RANGE

TECHNICAL DATA SHEET

ALL PURPOSE WALLPAPER ADHESIVE

1876 THE PROFESSIONAL RANGE



DESCRIPTION

Bartoline 1876 All Purpose Wallpaper Adhesive is a traditional, high quality, easy to mix flake adhesive. It is easily spread with excellent slip properties for accurate positioning and long-lasting results. Suitable for hanging all wallpaper types.

DIRECTIONS

Preparation: Ensure surface is clean, dry and free from dust. Treat areas where there is a high risk of mould growth with Bartoline Fungicidal Wash. Size absorbent surfaces before use and allow to dry completely before papering.

Mixing: Add the correct volume of cold water to a clean bucket based on the mix ratio table. Sprinkle the contents of the sachet into the water and stir briskly for 30 seconds to evenly mix. Leave to stand for 3 minutes then stir again thoroughly. The paste is now ready to use.

Pasting: Follow the wallpaper manufacturer's instructions. Soak heavy and embossed paper until supple. Paste generously, particularly the edges, and do not overspread. Take care to avoid getting adhesive on the patterned side of the paper, removing any splashes with a damp sponge. When applying paste the wall wallpapers apply paste directly onto the surface to be papered.

PACKING SPECIFICATION

Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
5 Roll	59942820	5010789942823	05010789840945	40	54	2160	9	6
10 Roll	59942830	5010789942830	05010789785475	25	54	1350	9	6
30 Roll	59942840	5010789942847	05010789775445	10	30	300	6	5

TECHNICAL DATA

Measurement	Value	Test Method
Physical State	Fine Scalings	Visual
Colour	Off White	Visual
Odour	Wallpaper paste	N/A
Flash Point	N/A	N/A
VOC content	None	N/A

MIX RATIO TABLES

5 Roll

Application	Quantity of cold water to use per sachet	Approximate coverage per sachet
Normal wallpapers	6 Pints / 3.4 Litres	4 - 5 Rolls
Vinyl wallcoverings	5 Pints / 2.8 Litres	4 Rolls
Blown vinyl wallcoverings	5 Pints / 2.8 Litres	4 Rolls
Embossed papers	4 Pints / 2.3 Litres	2 - 2.5 Rolls
Heavy Embossed papers	3.5 Pints / 2.0 Litres	1.75 - 2 Rolls
Paste the walls	4 Pints / 2.3 Litres	1.5 - 3 Rolls
Polystyrene tiles	4 Pints / 2.3 Litres	80 sq ft / 24m ²

*NB: These figures are intended as a guide only.

SIZING: When sizing walls before papering, mix contents into 8 Pints / 4.5 Litres of cold water.

10 Roll

Application	Quantity of cold water to use per sachet	Approximate coverage per sachet
Normal wallpapers	12 Pints / 7 Litres	8 - 10 Rolls
Vinyl wallcoverings	10 Pints / 5.7 Litres	8 Rolls
Blown vinyl wallcoverings	10 Pints / 5.7 Litres	8 Rolls
Embossed papers	8 Pints / 4.5 Litres	4 - 5 Rolls
Heavy Embossed papers	7 Pints / 4 Litres	3 - 4 Rolls
Paste the walls	8 Pints / 4.5 Litres	2 - 4 Rolls
Polystyrene tiles	8 Pints / 4.5 Litres	48m ²

*NB: These figures are intended as a guide only.

SIZING: When sizing walls before papering, mix contents into 16 Pints / 9 Litres of cold water.

30 Roll

As per 10 Roll as each box contains 3 x 10 Roll sachets.

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3505 1050.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.