



— 1876 —
THE PROFESSIONAL RANGE



TECHNICAL DATA SHEET

FLEXIBLE DECORATORS CAULK

1876 THE PROFESSIONAL RANGE

DESCRIPTION

Bartoline 1876 Flexible Decorators Caulk is a high performance product for the professional user based on leading developments in acrylic elastomer technology. It is ideal for sealing around frames, skirtings and architraves and general gap filling. Bartoline Flexible Decorators Caulk provides good flexibility combined with excellent colour stability and can be overpainted with waterborne paints after 1 hour* and solvent based paints when cured.

PREPARATION

Surfaces must be solid, clean, dry and free from grease and dust. Where a particularly neat finish is required, use masking tape to cover the face edges of the joint and remove immediately once tooling is completed.

DIRECTIONS

Non-porous surfaces such as aluminium should be cleaned with a suitable product. For application where some movement will be exhibited i.e. construction joints, the minimum joint dimensions should be 6mm x 6mm with the maximum dimensions being 25mm wide by 12mm deep. Where deeper joints are found, depth can be reduced using a suitable backer rod. Areas of perimeter pointing where a fillet is to be applied, the minimum measurement across must be 10mm with a minimum depth of 6mm. If conditions are suitable for application ensure joints are properly prepared, and apply sealant firmly into the joint using an application gun. Ensure a good solid fill is achieved. Once applied, sealant can be tooled to required finish. A degree of natural shrinkage will occur as a result of drying so it is advisable to apply the sealant slightly proud of the required level to allow for this. Surrounding surface and tools can be cleaned with water.

TECHNICAL DATA

EN ISO11600 F 12.5P

CE marked BS EN 15651 Perimeter frame and joint sealant Type F-EXT-INT

Composition	A blend of acrylic polymers and selected fillers
Specific Gravity	1.64 - 1.68
Tack Free Time	15 - 60 mins, dependent on thickness, ambient temperature and humidity
Full Cure	1 week - dependent on thickness, ambient temperature and humidity
Slump Resistance	Good. May be used in joints up to 25mm wide and 20mm deep
Application Temp. Range	+5°C - +40°C
Service Temp. Range	-20°C - +70°C
Life Expectancy	When applied correctly the sealant will perform satisfactorily for up to 12 years

PACKING SPECIFICATION

Size	Colour	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
310ml	White	52760090	5010789760090	05010789285524	12	132	1584	33	4
380ml	White	52760100	5010789760108	05010789865047	12	99	1088	33	3

LIMITATIONS

1876 Bartoline Flexible Decorators Caulk should not be applied at temperatures below 5°C, or in areas of constant water immersion.

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3214 9000.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.