



— 1876 —
THE PROFESSIONAL RANGE



TECHNICAL DATA SHEET

MULTI PURPOSE POWDER FILLER

1876 THE PROFESSIONAL RANGE

DESCRIPTION

Bartoline 1876 Multi Purpose Powder Filler has been specially developed for the professional user. Its non-shrink, non-slump formula is ideal for repairs to plaster, plasterboard, wood, brick, blockwork and most other building materials. Easily sanded, Bartoline Multi Purpose Powder Filler combines excellent adhesive properties that keeps the filler firmly in position with dry strength and capable of taking wallplugs, nails and screws when set. Bartoline Multi Purpose Powder Filler will not flash or grin when overcoated and is also suitable for exterior use providing it is sealed with an oil-based paint or varnish when dry.

PREPARATION

For best results brush out loose material and dust from the area to be filled. Hairline cracks should be slightly enlarged to ensure good filler penetration. Lightly moisten highly absorbent surfaces with water prior to application. Touch in nail and screw heads with an oil-based paint to prevent rusting. No need to prime or seal the surface before application.

MIXING

Only mix a quantity that can be used within maximum 40 minutes working time. Add approximately 2.5 parts filler to 1 part clean, cold water. Mix to a SMOOTH, stiff paste. Use a thicker mix for deep cracks or holes. Always use a clean container for mixing as soiled containers can affect the drying time.

APPLICATION & FINISH

Apply manually using a filling knife or trowel and press firmly into the cavity to be filled. Suitable for depths up to 10mm. Rub down with sandpaper as necessary when dry. When dry, can be over-coated with any type of filler, paint or wallcovering without priming. Do not use externally when rain is imminent. When used outdoors protect the filled area from rain and moisture during setting and then seal area with an oil-based paint or varnish to protect from weathering.

Tel: 01482 678710 | Fax: 01482 872606 | E-mail: info@bartoline.co.uk | www.bartoline.co.uk

VERSION 1 DATED 21.05.2022

TECHNICAL DATA

| Measurement | Value | Test Method |
|----------------|-----------------------|---------------------------|
| Physical State | Fine Powder | Visual |
| Colour | White | Visual |
| Odour | Plaster of Paris type | N/A |
| Flash Point | N/A | N/A |
| VOC content | None | N/A |
| pH | 6.5 - 7.8 | 280g powder to 120g water |

PACKING SPECIFICATION

| Size | Product Code | Pack Barcode | Carton Barcode | Packs Per Carton | Cartons Per Pallet | Packs Per Pallet | Ti | Hi |
|-------|--------------|---------------|----------------|------------------|--------------------|------------------|----|----|
| 1.5kg | 52710750 | 5010789710750 | 05010789155629 | 6 | 65 | 390 | 13 | 5 |
| 4.5kg | 52710483 | 5010789710484 | N/A | 1 | 60 | 60 | 10 | 6 |
| 9kg | 52710760 | 5010789710767 | N/A | 1 | 48 | 48 | 8 | 6 |

CLEANING & STORAGE

Remove excess filler from tools prior to cleaning. Clean tools and mixing vessels with warm water before filler sets. STORE IN A DRY PLACE KEEPING SACHET CLOSED. Dispose of any unused product and packaging responsibly in accordance with local and national regulations.

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3214 1090.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.

Tel: 01482 678710 | Fax: 01482 872606 | E-mail: info@bartoline.co.uk | www.bartoline.co.uk

VERSION 1 DATED 21.05.2022