



— 1876 —
THE PROFESSIONAL RANGE

TECHNICAL DATA SHEET

R/M LIGHT GRADE WALLCOVERING ADHESIVE

1876 THE PROFESSIONAL RANGE



DESCRIPTION

Bartoline 1876 Ready Mixed Light Grade Wallcovering Adhesive is a technically advanced wallpaper adhesive suitable for all types of wallcoverings including vinyl, blown vinyl, heavy embossed, washables and 'paste the wall' wallcoverings. No mixing or dilution is required. The super smooth easy spread adhesive has strong grab and easy slide properties for perfect wallpaper hanging.

COVERAGE

1kg of Bartoline 1876 Ready Mixed Light Grade Wallcovering Adhesive is sufficient to hang approximately one 10 metre roll of standard wallcovering, or half a roll of embossed or heavy embossed wallcovering.

DIRECTIONS

Preparation: Surfaces should be sound, dry, clean and free from damp, dust and grease. Gloss painted surfaces should be sanded to provide a key. Very porous surfaces such as new plaster should be sealed with PVA or Size.

Application: To open: break seal and lift lid. Always follow the wallcovering manufacturer's instructions. For traditional wallcoverings apply Bartoline 1876 Ready Mixed Light Grade Wallcovering Adhesive by brush or roller to the reverse of the wallcovering ensuring complete and even coverage. Avoid getting the adhesive on the patterned side of the paper. For heavy coverings allow time for the paste to soak until supple. Immediately remove any paste that comes into contact with patterned sides of the wallcovering.

For 'Paste The Wall' wallcoverings apply 1876 The Professional Range Ready Mix Wallcovering Light evenly and generously onto the wall surface, ensuring that the pasted area is slightly wider than the width of the wallpaper.

TECHNICAL DATA

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	Off White	Visual
Odour	PVA Type	N/A
Flash Point	N/A	N/A
VOC content	None	N/A
Viscosity	550 - 650 Poise	Lamy MSR4
pH	6.0 - 7.0	N/A

PACKING SPECIFICATION

Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
2.5kg	58511166	5010789511166	N/A	N/A	N/A	180	30	6
5kg	58511140	5010789511142	N/A	N/A	N/A	100	25	4
10kg	58511150	5010789511159	N/A	N/A	N/A	48	12	4

CLEANING & STORAGE

Any accidental splashes should be removed immediately with a clean, damp cloth or sponge. Tools and equipment should be cleaned with water immediately after use. Protect from frost.

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3506 9900.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.