



— 1876 —
THE PROFESSIONAL RANGE

TECHNICAL DATA SHEET

EXTERIOR MASONRY FILLER

1876 THE PROFESSIONAL RANGE



DESCRIPTION

Bartoline 1876 Exterior Masonry Filler has been specially developed for the professional user. Its cement-based formulation is ideal for repairing cracks, holes and gaps in exterior rendering, brick, stone, wood and most other building materials. Bartoline Exterior Masonry Filler combines excellent adhesive properties that keeps the filler firmly in position with dry strength capable of taking wallplugs, nails and screws when set. It allows a wide range of applications including the setting of non-structural bolts.

PREPARATION

For best results brush out loose material and dust from the area to be filled. Hairline cracks should be slightly enlarged to ensure good filler penetration. Lightly moisten highly absorbent surfaces with water prior to application. Touch in nail and screw heads with an oil-based paint to prevent rusting. No need to prime or seal the surface before application.

MIXING

Only mix an amount that can be used within 60 minutes. Add approximately 2.5 parts filler to 1 part clean, cold water. Mix to a SMOOTH, stiff paste. Use a thicker mix for deep cracks or holes. Always use a clean container for mixing as soiled containers can affect the drying time.

APPLICATION & FINISH

Apply manually using a filling knife or trowel and press firmly into the cavity to be filled removing any excess. Suitable for depths up to 10mm depth. If a deeper repair is required, build up the filler in stages. Do not use thinly over large areas. Do not use if frost or freezing conditions are expected. After setting overnight, the filler can be left unpainted or sealed with an oil-based paint or varnish to protect from weathering.

TECHNICAL DATA

Measurement	Value	Test Method
Physical State	Powder	Visual
Colour	Grey	Visual
Odour	PVA Type	N/A
Flash Point	N/A	N/A
Viscosity	2400 - 4400 Poise	Helipath Spindle TF/Speed 10 Mix Ratio 300g to 75g Water
pH	11.5 - 12.5	N/A

PACKING SPECIFICATION

Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
1.5kg	52710771	5010789710774	05010789155629	6	65	390	13	5
4.5kg	52710494	5010789710491	N/A	1	60	60	10	6

CLEANING & STORAGE

Remove excess filler from tools prior to cleaning. Clean tools and mixing vessels with warm water before filler sets. STORE IN A DRY PLACE KEEPING SACHET CLOSED. Dispose of any unused product and packaging responsibly in accordance with local and national regulations.

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3214 1090.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.