



— 1876 —
THE PROFESSIONAL RANGE

TECHNICAL DATA SHEET

INTERIOR WOOD FILLER

1876 THE PROFESSIONAL RANGE



DESCRIPTION

Bartoline 1876 Interior Wood Filler is a high quality ready to use filler developed for the professional user. Its formulation is ideal for all types of repairs to wood, including window frames, doors and skirting boards. Bartoline Interior Wood Filler dries white and can be stained, painted or varnished. It has strong adhesive properties and flexibility allowing for a wide range of wood applications.

PREPARATION

Ensure surfaces to be filled are clean, dry and dust free. Hairline cracks should be slightly enlarged to ensure good filler penetration. Touch in nail and screw heads with an oil-based paint to prevent rusting.

DIRECTIONS

If necessary, stir filler before use to an even, smooth consistency. Apply direct from the tub using a filling knife or trowel and press firmly into the cavity, smooth over the surface and allow to dry. Suitable for depths up to maximum 6mm. For best results, when set, protect the filler from excessive weathering with a suitable exterior paint or varnish. Do not use on surfaces regularly under water.

CLEANING & STORAGE

After use, ensure lid is firmly replaced to prevent contents from drying. Remove excess filler from tools prior to cleaning. Clean tools with water before filler sets hard. PROTECT FROM FROST.

TECHNICAL DATA

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White	Visual
Odour	PVA Type	N/A
Flash Point	N/A	N/A
VOC content	None	N/A
Viscosity	3500 - 4500 Poise	Lamy MSR4

PACKING SPECIFICATION

Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
1kg	52720278	5010789720278	05010789844516	6	96	576	12	8

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3214 1090.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.