



TECHNICAL DATA SHEET

RAPID FILL LIGHTWEIGHT FILLER

1876 THE PROFESSIONAL RANGE

DESCRIPTION

Bartoline 1876 Rapid Fill Lightweight Filler is a high quality easy to apply filler developed for the professional user. Its non-sagging formulation is ideal for repairs to plaster, brick, stone, wood, render and most other building materials. Suitable for interior and exterior use and dries a super white with a perfectly smooth finish. Bartoline Rapid Fill Lightweight Filler will fill large cracks and gaps with no need to build layers, as no shrinkage will be evident, even on ceilings.

PREPARATION

Ensure surfaces to be filled are clean, dry and dust free. Hairline cracks should be slightly enlarged to ensure good filler penetration. Lightly moisten highly absorbent surfaces with water prior to application. Touch in nail and screw heads with oil-based paint to prevent rusting.

DIRECTIONS

If necessary, stir filler before use to an even, smooth consistency. Apply direct from the tub using a filling knife or trowel and press firmly into the cavity, smooth over the surface and allow to dry. Suitable for depths up to maximum 75mm and widths up to 50mm. Although not normally necessary, the product may be sanded if required. When used outdoor, protect the filled area from rain and moisture until set. For best results, when set, protect the filler from excessive weathering with a suitable exterior paint or varnish.

CLEANING & STORAGE

After use, ensure lid is firmly replaced to prevent contents from drying. Remove excess filler from tools prior to cleaning. Clean tools with water before filler sets hard. PROTECT FROM FROST.

TECHNICAL DATA

Measurement	Value			
Physical State	Lightweight Paste			
Colour	White			
Density	0.30 to 0.36g /cm² (approx)			
Solid Content	62% w/w			
Maximum Fill	75mm in one coat			
Maximum Width	50mm			
Application Temp	5 - 30°C			

PACKING SPECIFICATION

Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
600ml	52740010	5010789740016	05010789723644	6	77	462	11	7
1.5L	52741500	5010789741501	05010789421229	6	63	378	9	7

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3214 1090.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.