



— 1876 —
THE PROFESSIONAL RANGE

TECHNICAL DATA SHEET

READY TO USE RAPID FILL EXTERIOR RENDER REPAIR

1876 THE PROFESSIONAL RANGE



DESCRIPTION

Bartoline 1876 Ready to Use Rapid Fill Exterior Render Repair has been specially developed for the professional user. Its formulation is ideal for outdoor repairs to brick, render, stone and most other building materials prior to painting.

PREPARATION

Ensure surfaces to be filled are clean, dry and dust free. Hairline cracks should be slightly enlarged to ensure good filler penetration. Touch in nail and screw heads with oil-based paint to prevent rusting. Do not apply when rain is imminent or in temperatures below 5°C.

DIRECTIONS

If necessary, stir filler before use to an even, smooth consistency. Apply manually using a filling knife or trowel and press firmly into the repair to be filled. Suitable for depths up to maximum 5mm. In larger areas, apply filler in layers of no more than 5mm thick, allowing each layer to dry for 1-2 hours before applying the next. For best results, when set, protect the repair from excessive weathering with a suitable exterior paint or varnish.

CLEANING & STORAGE

After use, ensure lid is firmly replaced to prevent contents from drying. Remove excess filler from tools prior to cleaning. Clean tools with water before filler sets hard. PROTECT FROM FROST.

TECHNICAL DATA

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White / Off White	Visual
Odour	PVA Type	N/A
VOC content	Minimal	N/A
Viscosity	4700 - 5300 Poise	Lamy MSR4
pH	8.5 - 9.5	N/A

PACKING SPECIFICATION

Size	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	Cartons Per Pallet	Packs Per Pallet	Ti	Hi
2.5kg	52729235	5010789729233	05010789189013	6	42	252	7	6
5kg	52729150	5010789729158	05010789190804	2	60	120	15	4

HEALTH & SAFETY

See MSDS for full information.

CUSTOMS TARIFF CODE

3214 1090.

SHIPPING CLASSIFICATION

Non-Hazardous for shipping purposes.